




Ex-d EXIOS Cable Glands

Ex-d Nickel Plated Brass & Stainless Steel Glands

Ex-e Nylon Glands

Ex-e Multi-Hole & Romex Glands

**Hex Plugs: (303) Stainless Steel Ex-e - Metric & PG Threads, IP 68/69K, NEMA 6, 150 PSIG, 10 BAR**

Part Numbers			Thread Type & Size	Dimensions in Inches (mm)			
-4°F to 203°F (-20°C to 95°C)	-4°F to 356°F (-20°C to 180°C)	-78°F to 356°F (-60°C to 180°C)		H	T	X	
			Page 59 for Thread Specs	Overall Height	Thread Length	Wrench Flat	
Buna-N	FPM	Silicone					
HM-12-SX	HM-12-SX-V	HM-12-SX-S		M12 x 1.5	.37 (9.5)	.26 (6.5)	.55 (14)
HM-16-SX	HM-16-SX-V	HM-16-SX-S		M16 x 1.5	.35 (9)	.24 (6)	.75 (19)
HM-20-SX	HM-20-SX-V	HM-20-SX-S		M20 x 1.5	.37 (9.5)	.24 (6)	.87 (22)
HM-25-SX	HM-25-SX-V	HM-25-SX-S		M25 x 1.5	.41 (10.5)	.28 (7)	1.18 (30)
HM-32-SX	HM-32-SX-V	HM-32-SX-S		M32 x 1.5	.49 (12.5)	.31 (8)	1.61 (41)
HM-40-SX	HM-40-SX-V	HM-40-SX-S		M40 x 1.5	.51 (13)	.31 (8)	1.81 (46)
HM-50-SX	HM-50-SX-V	HM-50-SX-S		M50 x 1.5	.59 (15)	.35 (9)	2.17 (55)
HM-63-SX	HM-63-SX-V	HM-63-SX-S		M63 x 1.5	.65 (16.5)	.39 (10)	2.76 (70)
HP-07-SX	HP-07-SX-V	HP-07-SX-S	PG 7	.31 (8)	.20 (5)	.55 (14)	
HP-09-SX	HP-09-SX-V	HP-09-SX-S	PG 9	.35 (9)	.24 (6)	.67 (17)	
HP-11-SX	HP-11-SX-V	HP-11-SX-S	PG 11	.37 (9.5)	.24 (6)	.79 (20)	
HP-13-SX	HP-13-SX-V	HP-13-SX-S	PG 13.5	.39 (10)	.26 (6.5)	.87 (22)	
HP-16-SX	HP-16-SX-V	HP-16-SX-S	PG 16	.39 (10)	.26 (6.5)	.94 (24)	
HP-21-SX	HP-21-SX-V	HP-21-SX-S	PG 21	.41 (10.5)	.28 (7)	1.18 (30)	
HP-29-SX	HP-29-SX-V	HP-29-SX-S	PG 29	.49 (12.5)	.31 (8)	1.61 (41)	
HP-36-SX	HP-36-SX-V	HP-36-SX-S	PG 36	.51 (13)	.31 (8)	1.97 (50)	
HP-42-SX	HP-42-SX-V	HP-42-SX-S	PG 42	.59 (15)	.35 (9)	2.28 (58)	
HP-48-SX	HP-48-SX-V	HP-48-SX-S	PG 48	.65 (16.5)	.39 (10)	2.56 (65)	

Silicone version accommodates **-60°C** Temperature

AISI 303 Stainless Steel Hex Plugs



**Hex Plugs - Accessories - Nickel Plated Brass & (316L) Stainless Steel - NPT / Metric - Ex-d/Ex-e**







Ex-e Nickel Plated Brass & Stainless Steel Glands

Ex-e EMI / RFI Nickel Plated Brass Glands

Ex-e / Ex-d Accessories

Technical Information


**Hex Plugs: Nickel Plated Brass & (316L) Stainless Steel Ex-d/Ex-e - Metric Threads, IP 68/69K, NEMA 6, 150 PSIG, 10 BAR**

Part Numbers - Nickel Plated Brass *			Part Numbers - Stainless Steel **			Thread Type & Size	Dimensions in Inches (mm)				
-4°F to 203°F (-20°C to 95°C)	-4°F to 356°F (-20°C to 180°C)	-76°F to 356°F (-60°C to 180°C)	-4°F to 203°F (-20°C to 95°C)	-4°F to 356°F (-20°C to 180°C)	-76°F to 356°F (-60°C to 180°C)		H	H	T	X	
						Page 59 for Thread Specs	Overall Height (Nickel Plated Brass)	Overall Height (Stainless Steel)	Thread Length	Wrench Flat	
Buna-N	Viton	Silicone	Buna-N	Viton	Silicone						
HN-38-MX-D*			HN-38-6X-D*				NPT 3/8"	.79 (20)	.79 (20)	.63 (16)	*.63 (16) & **.75 (19)
HN-12-MX-D*			HN-12-6X-D*				NPT 1/2"	.93 (23.5)	.93 (23.5)	.79 (20)	.75 (24)
HN-34-MX-D*			HN-34-6X-D*				NPT 3/4"	.94 (24)	.94 (24)	.81 (20.5)	1.18 (30)
HN-10-MX-D*			HN-10-6X-D*				NPT 1"	1.16 (29.5)	1.16 (29.5)	.98 (25)	1.61 (41)
HN-54-MX-D*			HN-54-6X-D*				NPT 1 1/4"	1.22 (31)	1.22 (31)	1.02 (26)	1.81 (46)
HN-64-MX-D*			HN-64-6X-D*			NPT 1 1/2"	1.27 (32.5)	1.27 (32.5)	1.04 (26.5)	2.17 (55)	
HM-12-MX-D	HM-12-MX-D	HM-12-MIX-D	HM-12-6X-D	HM-12-6VX-D	HM-12-6IX-D	M12 x 1.5	.67 (17)	.75 (19)	.63 (16)	.55 (14)	
HM-16-MX-D	HM-16-MX-D	HM-16-MIX-D	HM-16-6X-D	HM-16-6VX-D	HM-16-6IX-D	M16 x 1.5	.63 (16)	.75 (19)	.63 (16)	.75 (19)	
HM-20-MX-D	HM-20-MX-D	HM-20-MIX-D	HM-20-6X-D	HM-20-6VX-D	HM-20-6IX-D	M20 x 1.5	.61 (15.5)	.77 (19.5)	.63 (16)	.87 (22)	
HM-25-MX-D	HM-25-MX-D	HM-25-MIX-D	HM-25-6X-D	HM-25-6VX-D	HM-25-6IX-D	M25 x 1.5	.61 (15.5)	.77 (19.5)	.63 (16)	1.18 (30)	
HM-32-MX-D	HM-32-MX-D	HM-32-MIX-D	HM-32-6X-D	HM-32-6VX-D	HM-32-6IX-D	M32 x 1.5	.65 (16.5)	.81 (20.5)	.63 (16)	1.61 (41)	
HM-40-MX-D	HM-40-MX-D	HM-40-MIX-D	HM-40-6X-D	HM-40-6VX-D	HM-40-6IX-D	M40 x 1.5	.67 (17)	.83 (21)	.63 (16)	1.81 (46)	
HM-50-MX-D	HM-50-MX-D	HM-50-MIX-D	HM-50-6X-D	HM-50-6VX-D	HM-50-6IX-D	M50 x 1.5	.71 (18)	.87 (22)	.63 (16)	2.17 (55)	
HM-63-MX-D	HM-63-MX-D	HM-63-MIX-D	HM-63-6X-D	HM-63-6VX-D	HM-63-6IX-D	M63 x 1.5	.73 (18.5)	.89 (22.5)	.63 (16)	2.76 (70)	

\*All NPT Hex Plugs do not come with an O-Ring.



AISI (316L) Stainless Steel Hex Plugs



Silicone version accommodates **-60°C** Temperature

