



For Non-Armored Cable

Nickel Plated Brass, Cable Glands with Romex® Inserts, Hazardous Duty Locations, V0, UL94, NEMA 6, IP 68						
Part Numbers	Slot Size	Thread Type & Size	Dimensions in Inches (mm)			
			A	B	C	F ₁ /F
-4°F to 203°F (-20°C to 95°C)			Clearance Hole	Body Length	Thread Length	Wrench Flats
Nickel Plated Brass  (Standard)	Inches (mm) H x W	Page 59 for Thread Specs	+ .01" (+.25 mm)	(Dome)	(Standard)	
CD21NS-EB1	.24 x .55 (6 x 14)	3/4" NPT	1.05 (26.7)	.98 (25)	.51 (13)	1.18 (30)
CD21NS-EB2	.28 x .55 (7 x 14)					
CD29NS-EB1	.31 x .87 (8 x 22)	1" NPT	1.35 (34.3)	1.14 (29)	.75 (19)	1.57 (40)
CD22MS-EB1	.24 x .55 (6 x 14)	M20 x 1.5	.79 (20)	.94 (24)	.24 (6)	.94 (24)
CD22MS-EB2	.28 x .47 (7 x 12)					
CD25MS-EB1	.24 x .55 (6 x 14)	M25 x 1.5	.98 (25)	1.02 (26)	.28 (7)	1.18 (30)
CD25MS-EB2	.28 x .55 (7 x 14)					
CD32MS-EB1	.31 x .87 (8 x 22)	M32 x 1.5	1.26 (32)	1.22 (31)	.31 (8)	1.57 (40)
CD40MS-EB1	.39 x 1.12 (10 x 28.5)	M40 x 1.5	1.57 (40)	1.46 (37)	.31 (8)	1.97 (50)
CD40MS-EB2	.20 x 1.14 (5.5 x 29)					
CD40MS-EB3	.47 x 1.20 (12 x 30.5)					
CD40MS-EB4	.29 x 1.22 (7.5 x 31)					
CD50MS-EB1	.45 x 1.31 (11.5 x 33.5)	M50 x 1.5	1.97 (50)	1.46 (37)	.35 (9)	2.24 (57)
CD63MS-EB1	.47 x 1.50 (12 x 38)	M63 x 1.5	2.48 (63)	1.49 (38)	.39 (10)	2.52 (64) / 2.68 (68)
CD16AS-EB1	.24 x .55 (6 x 14)	PG 16	.89 (22.5)	.91 (23)	.26 (6.5)	.94 (24)
CD16AS-EB2	.28 x .47 (7 x 12)					
CD21AS-EB1	.24 x .55 (6 x 14)	PG 21	1.12 (28.4)	.94 (24)	.28 (7)	1.18 (30)
CD21AS-EB2	.28 x .55 (7 x 14)					
CD29AS-EB1	.31 x .87 (8 x 22)	PG 29	1.47 (37.3)	1.14 (29)	.31 (8)	1.57 (40)
CD36AS-EB1	.39 x 1.12 (10 x 28.5)	PG 36	1.85 (47)	1.37 (35)	.31 (8)	1.97 (50)
CD36AS-EB2	.20 x 1.14 (5.5 x 29)					
CD36AS-EB3	.47 x 1.18 (12 x 30)					
CD36AS-EB4	.29 x 1.22 (7.5 x 31)					
CD42AS-EB1	.45 x 1.31 (11.5 x 33.5)	PG 42	2.13 (54.1)	1.46 (37)	.35 (9)	2.24 (57)
CD48AS-EB2	.47 x 1.50 (12 x 38)	PG 48	2.34 (59.4)	1.49 (38)	.39 (10)	2.52 (64)

ROMEX® is a federally registered trademark of Southwire Company.

Cable Glands with Inserts for Flat Cables

These form seals are also available with Cable Glands made of other materials. (Nickel Plated Brass, Stainless Steel, etc.)



*** Additional UL Information**

- Our FLAKA (for Romex® style cable) HSK-K-Ex PG16 are UL listed (UL file # E168975)
- To meet UL, only Romex® style cable (flat top and bottom) can be used with this style Cable Gland (No Zip Cable, No Ribbon cable, etc.)



Ex-d EXIOS Cable Glands
 Ex-d Nickel Plated Brass & Stainless Steel Glands
 Nylon Glands
 Ex-e Multi-Hole & Romex Glands
 Ex-e Nickel Plated Brass & Stainless Steel Glands
 Ex-e EMI / RFI Nickel Plated Brass Glands
 Ex-e / Ex-d Accessories
 Technical Information